

HYDX



Program Encryption

E200 Professional FM Transceiver

2W CTCSS/DCS 支持非标亚音
CTCSS/DCS Support Non-standard

- 16 Channels
- 省电功能 Battery Save
- 发射限时功能 TOT
- 繁忙信道锁定 BCLO
- 电脑软件编程 PC Programmable
- 静音消除 Tail Elimination
- 静噪电平可调 SQL
- 读写频加密 Program Encryption

HYDX

E200 Professional FM Transceiver

功能特点 Main Functions

- 频率范围UHF 400-520MHz/VHF 136-174MHz
- 16 信道
- 声控VOX
- 中英文语音报号
- 电脑软件编程
- CTCSS/DCS 非标亚音频
- 省电功能
- 静音消除
- 发射限时功能
- 静噪电平可调
- 扫描
- 读写频加密
- 繁忙信道锁定
- Frequency UHF 400-520MHz/VHF 136-174MHz
- 16 Channels
- VOX
- Chinese/English Voice Report
- PC Programmable
- CTCSS/DCS Support Non-standard
- Battery Save
- Tail Elimination
- TOT
- SQL
- Scan
- Program Encryption
- BCLO

技术参数 Technical Specification

整机部分 GENERAL		发射部分 TRANSMITTER		接收部分 RECEIVER	
可用频率范围 Frequency Range	UHF: 400-520MHz 200-260 MHz VHF: 136-174MHz	输出功率 Output Power	2W	参考灵敏度 Reference Sensitivity	优于-122dBm
射频输出功率 RF Output Power	2W	调制 Modulation	F3E	邻道选择性 Adjacent Channel Selectivity	≥65 dB
信道数量 Channels	16	调制灵敏度 Modulation Sensitivity	12±5mV	互调 Inter-modulation	-55dB
信道间隔 Channel Spacing	宽带:25Khz 窄带:12.5Khz	邻道功率 Adjacent Channel Power	≤-65dB(WIDE) ≤-55 dB(Narrow)	S/N S/N	≥50 dB宽带 (WIDE) ≤-40 dB窄带 (Narrow)
亚音频 CTCSS/DCS	50 CTCSS/ 105 DCS	调制失真 Modulation Distortion	≤ 1%	额定输出功率 Rated Output Power	≤1W
天线阻抗 Antenna Impedence	50Ω			额定音频失真 Rated Audio Distortion	≤10%
工作温度 Operating Temperature	-20℃+50℃				
工作电压 Operating Voltage	DC3.7V				
电池类型 Battery Type	1200mAh锂电池 1200mAh Li-ion				
外形尺寸 (不含天线) Dimension(excluding antenna)	124(H) x 61(W) x 48.5(D)mm				
重量 (含天线、电池) Weight(Battery,Antenna included)	约250克 About 250g				

标准配件 Standard Accessories



华远电讯集团
福建省佳胜通电子设备有限公司
地址: 福建省泉州市鲤城区江南高新园元泰3路115、117、119号 邮编: 362000
销售热线: 0595-28563681
网址: www.odmradio.com

Huayuan Electron Communicate Group
Fujian Juston Electronic Equipment Co.,Ltd.
ADD: No.115,117,119,Yuantai 3rd Road ,Jiangnan Hi-tech Park,
Licheng District, Quanzhou ,Fujian, China 362000
Sales:86-595-2856-3681
Website:www.odmradio.com